















Accesorios forjados y roscados: ANSI B16.11 - BS3799 2-3-6000 lbs

		Serie	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
	Codo 90°	2000	0,008	0,150	0,225	0,280	0,460	0,800	1,00	1,60	2,30	4,35	10,25
		3000	0,140	0,265	0,365	0,600	1,08	1,22	4,45	2,50	5,25	7,40	13,00
		6000	0,310	0,500	0,685	1,50	1,65	2,75	3,22	6,25	10,00	17,00	14,50
	Codo 90° M/H	3000	0,131	0,225	0,325	0,530	0,940	1,30	1,47	2,30	-	-	-
	Codo 45°	2000	0,100	0,110	0,210	0,240	0,390	0,700	0,850	1,23	3,00	3,50	9,00
		3000	0,130	0,250	0,360	0,530	0,780	1,02	1,70	2,35	5,40	6,00	10,50
		6000	0,250	0,350	0,600	0,950	1,22	1,35	2,55	5,60	8,00	15,50	13,00
	Tree	2000	0,115	0,180	0,290	0,385	0,550	0,930	1,30	1,80	3,00	5,50	14,00
		3000	0,205	0,305	0,490	0,800	1,31	1,61	3,20	3,55	6,50	9,25	17,00
		6000	0,410	0,600	0,935	1,59	2,14	3,39	4,50	10,00	13,00	19,50	18,00
	Cruz	2000	0,140	0,190	0,335	0,420	0,750	1,15	1,45	2,25	4,50	7,15	15,00
		3000	0,220	0,400	0,630	0,990	1,63	1,97	3,70	4,90	10,50	11,50	21,70
		6000	0,450	0,700	1,16	1,80	2,50	4,10	5,20	12,30	14,00	25,00	23,00
	Cupla	3000	0,056	0,066	0,140	0,200	0,390	0,730	1,03	1,35	2,30	3,15	5,80
		6000	0,105	0,115	0,370	0,450	1,00	1,65	1,85	2,80	4,00	5,50	10,00
	Media Cupla	3000	0,028	0,033	0,070	0,110	0,195	0,365	0,510	0,660	1,15	1,57	2,90
		6000	0,053	0,058	0,185	0,225	0,500	0,830	0,920	1,40	2,00	2,75	5,00
	Tapa	3000	0,047	0,058	0,125	0,210	0,370	0,600	0,730	1,10	2,31	3,00	4,50
		6000	0,160	0,200	0,290	0,395	0,700	1,10	1,35	2,10	3,50	4,80	7,50
	Tapón macho	CC 3000	0,016	0,028	0,048	0,090	0,170	0,273	0,400	0,600	0,890	1,25	3,10
		CE 6000	0,026	0,047	0,071	0,130	0,218	0,410	0,490	0,770	1,61	1,94	4,50
		CR	0,048	0,070	0,130	0,220	0,320	0,500	0,720	1,35	2,20	3,30	6,00
	Buje reducción	6000	0,016	0,021	0,032	0,063	0,120	0,209	0,212	0,450	0,760	1,00	2,50
		6000	-	0,032	0M047	0,083	0,150	0,280	0,314	0,513	1,14	1,35	2,90
		6000	-	-	0,057	0,098	0,173	0,330	0,418	0,620	1,27	1,65	3,10
		6000	-	-	-	0,170	0,195	0,400	0,490	0,690	1,41	1,80	3,52
		6000	-	-	-	-	0,214	0,480	0,540	0,704	1,53	2,00	3,85
	Rosca con tuerca	2000 STD-XS	0,028	0,047	0,070	0,110	0,182	0,300	0,360	0,500	0,960	1,40	2,40
		3000 Sch.160	0,030	0,055	0,080	0,145	0,236	0,372	0,452	0,760	1,30	1,95	3,30
		6000 XXS	-	-	0,120	0,170	0,303	0,516	0,626	0,930	1,80	2,50	4,00
	Unión doble cónica	3000	0,167	0,211	0,305	0,490	0,830	1,22	1,53	2,30	5,00	6,25	14,50
		6000	0,300	0,500	1,12	1,60	2,15	2,42	4,73	6,50	9,50	19,20	23,00
	Unión doble macho - hembra	3000	0,210	0,274	0,462	0,610	0,985	1,55	1,90	2,86	-	-	-
	Niples	STD	0,060	0,080	0,125	0,165	0,240	0,330	0,400	0,530	0,850	1,10	1,30
		XS	0,075	0,105	0,155	0,215	0,305	0,435	0,530	0,740	1,12	1,46	2,15
		Sch.160	-	-	0,190	0,280	0,415	0,550	0,720	1,06	1,46	2,05	3,20
		XXS	-	-	0,250	0,355	0,540	0,770	0,950	1,31	2,00	2,65	4,00